

Vaultwarden

en vrac:

```
apt install mariadb-server mariadb-client libmariadb3 libpq5
wget
https://download.opensuse.org/repositories/home:/Masgalor:/Vaultwarden/Debian_11/amd64/vaultwarden_1.25.2-1+1.1_amd64.deb
wget
https://download.opensuse.org/repositories/home:/Masgalor:/Vaultwarden/Debian_11/all/vaultwarden-webvault_2022.6.2-1+12.1_all.deb
dpkg -i *.deb

nano /etc/apache2/sites-enabled/000-default.conf

<VirtualHost *:80>
    # The ServerName directive sets the request scheme, hostname and
port that
    # the server uses to identify itself. This is used when creating
    # redirection URLs. In the context of virtual hosts, the ServerName
    # specifies what hostname must appear in the request's Host: header
to
    # match this virtual host. For the default virtual host (this file)
this
    # value is not decisive as it is used as a last resort host
regardless.
    # However, you must set it for any further virtual host explicitly.
    #ServerName www.example.com

#    ServerAdmin webmaster@localhost
#    DocumentRoot /var/www/html

    # Available loglevels: trace8, ..., trace1, debug, info, notice,
warn,
    # error, crit, alert, emerg.
    # It is also possible to configure the loglevel for particular
    # modules, e.g.
    #LogLevel info ssl:warn

    ProxyPreserveHost On

    ProxyPass / http://127.0.0.1:8000/
    ProxyPassReverse / http://127.0.0.1:8000/

    Timeout 5400
    ProxyTimeout 5400
```

```
ServerName server
```

```
ErrorLog ${APACHE_LOG_DIR}/error.log
CustomLog ${APACHE_LOG_DIR}/access.log combined
```

```
# For most configuration files from conf-available/, which are
# enabled or disabled at a global level, it is possible to
# include a line for only one particular virtual host. For example
the
# following line enables the CGI configuration for this host only
# after it has been globally disabled with "a2disconf".
#Include conf-available/serve-cgi-bin.conf
</VirtualHost>
```

```
nano /etc/vaultwarden/vaultwarden.cfg
```

```
SIGNUPS_ALLOWED=false
SENDS_ALLOWED=true
# Note: if SMTP_USERNAME is specified, SMTP_PASSWORD is mandatory
SMTP_HOST=127.0.0.1
SMTP_FROM=vaultwarden@vault.creapix.eu
# SMTP_FROM_NAME=Vaultwarden
# SMTP_SECURITY=starttls # ("starttls", "force_tls", "off") Enable a secure
connection. Default is "starttls" (Explicit - ports 587 or 25), "force_tls"
(Implicit - port 465) or "off", no encryption (port 25)
SMTP_PORT=25
```

From:

<https://wiki.makeitsimple.be/> - **makeITsimple wiki**

Permanent link:

<https://wiki.makeitsimple.be/doku.php?id=linux:vaultwarden>

Last update: **2022/09/03 20:07**

