

Work in progress:

```
apt-get install libxml2-dev libxslt1-dev libsasl2-dev libldap2-dev libssl-
dev libffi-dev libjpeg-dev libpq-dev
```

```
drop sequence base_cache_signaling_default;
drop sequence base_cache_signaling_assets;
drop sequence base_cache_signaling_templates;
drop sequence base_cache_signaling_routing;
```

```
python3 <(curl -s https://upgrade.odoo.com/upgrade) test -d klinicare -t
17.0 --contract M240802164735325
```

```
psql
UPDATE pg_database SET datistemplate = FALSE WHERE datname = 'template1';
DROP DATABASE template1;
CREATE DATABASE template1 WITH TEMPLATE = template0 ENCODING = 'UTF8';
UPDATE pg_database SET datistemplate = TRUE WHERE datname = 'template1';
\c template1;
VACUUM FREEZE;
```

```
dropdb "klinicare_test_17.0_2024_09_17_17_51"
```

```
createdb -E utf8 klinicare_v17
psql klinicare_v17 < dump.sql
```

```
ALTER DATABASE klinicare_v17 OWNER TO odoo;
```

```
cp /var/lib/odoo/.local/share/Odoo/filestore/klinicare
/var/lib/odoo/.local/share/Odoo/filestore/klinicare_v17/ -r
vérifier les droits sur les dossiers du filestore
chown odoo:odoo * -R
```

désinstaller les modules non-officiels fermer le serveur faire un backup

```
su postgres -s /bin/bash
service odoo stop
dpkg -i
python3 /usr/bin/odoo -d klinicare -i web_enterprise --stop-after-init
```

Lancer la commande de maj

```
apt install rsync
```

```
su postgres -s /bin/bash
cd /tmp
# Changer test
python3 <(curl -s https://upgrade.odoo.com/upgrade) test -d klinicare -t
```

## 16.0 --contract xxxxxx

/var/lib/odoo/.local/share/Odoo/filestore/klinicare/

klinicare\_test\_16.0\_2024\_09\_02\_18\_10

When performing database restoration via the command line, ensure you have correctly placed the filestore. The database name and filestore name should match to ensure Odoo uses the same filestore rather than generating a new one. The filestore in Odoo is stored in /home/odoo/.local/share/Odoo/filestore (assuming /home/odoo is Odoo's home directory).

```
ALTER DATABASE "klinicare_test_16.0_2024_09_02_18_10" OWNER TO odoo;
```

```
SELECT format(  
    'ALTER TABLE public.%I OWNER TO odoo',  
    table_name  
)  
FROM information_schema.tables  
WHERE table_schema = 'public'  
    AND table_type = 'BASE TABLE' \gexec
```

```
SELECT format(  
    'ALTER TABLE public.%I OWNER TO odoo',  
    table_name  
)  
FROM information_schema.tables  
WHERE table_schema = 'public'  
    AND table_type = 'BASE TABLE' \gexec
```

```
drop sequence base_cache_signaling;  
drop sequence base_registry_signaling;  
drop sequence base_cache_signaling_default;  
drop sequence base_cache_signaling_assets;  
drop sequence base_cache_signaling_templates;  
drop sequence base_cache_signaling_routing;
```

From:  
<https://wiki.makeitsimple.be/> - **makeITsimple wiki**

Permanent link:  
<https://wiki.makeitsimple.be/doku.php?id=odoo:migration-ce-saas&rev=1726601412>

Last update: **2024/09/17 19:30**

