

Microsoft Edge: Autoriser les connexions locales non sécurisées

Dans l'adresse: taper Edge:flags/

Reset all

Expériences

103.0.1264.62

WARNING: EXPERIMENTAL FEATURES AHEAD! By enabling these features, you could lose browser data or compromise your security or privacy. Enabled features apply to all users of this browser. If you are an enterprise admin you should not be using these flags in production.

Disponible

Non disponible

● Allow invalid certificates for resources loaded from localhost.

Allows requests to localhost over HTTPS even when an invalid certificate is presented. – Mac, Windows, Linux, Android
[#allow-insecure-localhost](#)

Activé

● Block insecure private network requests.

Prevents non-secure contexts from making subresource requests to more-private IP addresses. – Mac, Windows, Linux, Android
[#block-insecure-private-network-requests](#)

Disabled

Temporarily unexpire M101 flags.

Temporarily unexpire flags that expired as of M101. These flags will be removed soon. – Mac, Windows, Linux, Android
[#temporary-unexpire-flags-m101](#)

Default

Temporarily unexpire M102 flags.

Temporarily unexpire flags that expired as of M102. These flags will be removed soon. – Mac, Windows, Linux, Android
[#temporary-unexpire-flags-m102](#)

Default

Override software rendering list

Overrides the built-in software rendering list and enables GPU-acceleration on unsupported

Désactivé

Ceci est peut-être valable sur Chrome

From: <https://wiki.makeitsimple.be/> - makeITsimple wiki

Permanent link: <https://wiki.makeitsimple.be/doku.php?id=windows:edge:insecure&rev=1658314384>

Last update: 2022/07/20 10:53



